

Primary Wire



General Purpose Primary Wire

Plastic primary single conductor wire, with durable thermoplastic PVC compound that resists chemical attack, abrasion and heat to 90°C (194°F). Clean stripping for easy use. Type GPT to SAE specification J1128.

Gauge	Length	Outside Diameter	Stranding	Part Numbers							
				Black	Blue	Brown	Green	Orange	Red	White	Yellow
Mini Spools											
18	50'	.091"	16 x .010"	68051	68052	68053	68054		68056	65057	68059
16	35'	.104"	19 x .0113"	68061	68062	68063	68064		68065	68066	68067
14	25'	.119"	19 x .0142"	68068	68069	68070	68071		68072	68073	68074
12	15'	.145"	19 x .0179"	68075	68076	68983	68922		68077	68078	68928
10	10'	.175"	19 x .0234"	68080	68906	68081	68980		68082	68981	68979
50' (15.2m) Spool											
10	50'	.175"	19 x .0234"	68102	68103	68104	68105		68106	68107	68108
100' (30.5m) Spool											
18	100'	.091"	16 x .010"	68000	68001	68002	68003		68005	68006	68007
16	100'	.104"	19 x .0113"	68010	68011	68012	68013	68014	68015	68016	68017
14	100'	.119"	19 x .0142"	68020	68021	68022	68023	68024	68025	68026	68027
12	100'	.145"	19 x .0179"	68030	68031	68032	68033		68035	68036	68037
8	100'	.239"	7 x 12 x .0142"	68050					68155		
6	100'	.285"	7 x 7 x .0226"	68060					68165		
4	100'	.354"	7 x 27 x .0142"						68175		
1000' (305m) Spool											
18	1000'	.091"	16 x .010"	68200	68201	68202	68203		68205	68206	68207
16	1000'	.104"	19 x .0113"	68210	68211	68212	68213	68214	68215	68216	68217
14	1000'	.119"	19 x .0142"	68220	68221	68222	68223	68224	68225	68226	68227
12	1000'	.145"	19 x .0179"	68230	68231	68232	68233	68234	68235	68236	68237
10	1000'	.175"	19 x .0234"	68240	68241	68242	68243		68245	68246	68247

SXL Heat Resistant Primary Wire

General purpose, low tension cable, crosslinked polyethylene insulated jacket provides toughness combined with outstanding heat, grease, oil, gasoline and chemical resistance. Clean stripping for easy use. Ideally suited for heavy-duty applications. 125°C (257°F) temp rating, 50 volt. chemical attack, abrasion and heat to 90°C (194°F). Clean stripping for easy use. Type GPT to SAE specification J1128.

Gauge	Outside Diameter	Stranding	Part Numbers							
			Black	Blue	Brown	Green	Orange	Red	White	Yellow
100' (30.5m) Spool										
16	.129"	19 x .0113"	68840	68841	68842	68843	68847	68844	68845	68846
14	.151"	19 x .0142"	68850	68851	68852	68853	68857	68854	68855	68856
12	.172"	19 x .0179"	68860	68861	68862	68863	68867	68864	68865	68866
10	.203"	19 x .0234"	68770			68773		68774	68775	68776
8	.226"	7 x 12 x .0142"	68780					68784	68785	

TEW 600 Volt Rated Primary Wire

For use in internal wiring of electrical equipment. Applications include electric ranges, heating equipment, lighting fixtures, panels and meters. Stranded copper conductor, PVC insulation, 600 volts, -40°C (-40°F) to 105°C (221°F) temp rating. Meets CSA and UL requirements.

Gauge	Outside Diameter	Stranding	Part Numbers								
			Black	Blue	Brown	Green	Orange	Red	White	Yellow	Grey
100' (30.5m) Spool											
16	.122"	26 x .010"	68609	68610	68611	68612	68613	68614	68615	68616	68617
14	.136"	41 x .010"	68618	68619	68620	68621	68622	68623	68624	68625	68626
12	.159"	65 x .010"	68627	68628	68629	68630	68631	68632	68633	68634	

Cable

Type GPT 2, 3 & 4 Conductor

General purpose, low-tension plastic, insulated cable with grey PVC outer jacket. SAE specification J1128.



Part #	Conductors /Gauge	Stranding	Red	Green	Black	White
100' (30.5 m)						
68430	2/16	19 x .0113"			•	•
68431	2/14	19 x .0142"			•	•
68432	2/12	19 x .0179"			•	•
68570	3/16	19 x .0113"		•	•	•
68571	3/14	19 x .0142"		•	•	•
68580	4/16	19 x .0113"	•	•	•	•
68581	4/14	19 x .0142"	•	•	•	•
1000' (305 m)						
68435	2/16	19 x .0113"			•	•
68436	2/14	19 x .0142"			•	•
68437	2/12	19 x .0179"			•	•
68475	3/16	19 x .0113"		•	•	•
68576	3/14	19 x .0142"		•	•	•
68585	4/16	19 x .0113"	•	•	•	•
68586	4/14	19 x .0142"	•	•	•	•

Type GPT 2 Conductor Parallel Jacketed PVC Cable

General purpose low-tension, plastic insulated cable with PVC compound insulation. Bonded parallel red and brown conductor SAE specification J1128.



Part #	Conductors /Gauge	Stranding	Length
68401	2/16	19 x .0113"	100' (30.5m) spool
68405	2/16	19 x .0113"	250' (76.2m) spool
68416	2/16	19 x .0113"	2500' (762m) spool

Speaker Wire Clear Two-Tone Vinyl Jacketed Cable

NEW

Bonded parallel conductors. Wire is polarized using bare copper stranding on one side and tin plated copper stranding on the other side.



Part #	Conductors /Gauge	Stranding	Length
68500	2/22	19 x .0113"	100' (30.5m) spool

Type GPT Parallel Jacketed 3 & 4 Conductor PVC Cable

General purpose, low-tension, plastic insulated cable with bonded parallel 3 and 4 conductor. SAE specification J1128.



Part #	Conductors /Gauge	Stranding	Green	Brown	Yellow	White
100' (30.5 m)						
68089	3/16	19 x .0113"	•	•	•	
68091	3/14	19 x .0142"	•	•	•	
68090	4/16	19 x .0113"	•	•	•	•
68092	4/14	19 x .0142"	•	•	•	•
250' (76 m)						
68481	4/16	19 x .0113"	•	•	•	•
1000' (305 m)						
68093	4/14	19 x .0142"	•	•	•	•

Trailer Cable

Premium Trailer Cable TPR

Cable remains flexible at -51°C (-59°F) and withstands temperature up to 149°C (300°F) with a high dielectric strength. Color-coded multiple conductors with a black TPR (thermoplastic rubber) outer jacket that resists abrasion and oil contamination. Recommended for rewiring trailers to ICC regulations.



Part No.	Conductors /Gauge	O.D.	Stranding	Yellow	Red	Green	Brown	Black	Blue	White
50' (15.2 m)										
69044	4/14	.450"	41 x .010"	•	•	•	•	•	•	•
69065	6/14	.560"	19 x .014"	•	•	•	•	•	•	•
69072	7/14	.570"	19 x .014"	•	•	•	•	•	•	•
69077	6/12, 1/10	.685"	65 x .014" (12ga.)	•	•	•	•	•	•	•
			106 x .010" (10ga.)	•	•	•	•	•	•	•
100' (30.5 m)										
69040	4/14	.450"	41 x .010"	•	•	•	•	•	•	•
69062	6/14	.560"	19 x .014"	•	•	•	•	•	•	•
69074	7/14	.570"	19 x .014"	•	•	•	•	•	•	•
69070	6/12, 1/10	.685"	65 x .014" (12ga.)	•	•	•	•	•	•	•
			106 x .010" (10ga.)	•	•	•	•	•	•	•
500' (152 m)										
69041	4/14	.450"	41 x .010"	•	•	•	•	•	•	•
69063	6/14	.560"	19 x .014"	•	•	•	•	•	•	•
69075	7/14	.570"	19 x .014"	•	•	•	•	•	•	•
69071	6/12, 1/10	.685"	65 x .014"	•	•	•	•	•	•	•
			106 x .010" (10ga.)	•	•	•	•	•	•	•

Economy Trailer Cable PVC

This low-cost, quality cable remains flexible at -70°C (-94°F) and withstands temperature up to 60°C (140°F) with a high dielectric strength. Color-coded multiple conductors with a black PVC outer jacket that resists abrasion and oil contamination. Recommended for rewiring trailers to ICC regulations.

Part No.	Conductors /Gauge	O.D.	Stranding	Yellow	Red	Green	Brown	Black	Blue	White
50' (15.2 m)										
69086	4/14	.444"	41 x .010"	•	•	•	•	•	•	•
69091	6/14	.562"	41 x .010"	•	•	•	•	•	•	•
69084	7/14	.562"	41 x .010"	•	•	•	•	•	•	•
69083	6/14, 1/12	.565"	41 x .010" (14ga.)	•	•	•	•	•	•	•
			65 x .010" (12ga.)	•	•	•	•	•	•	•
69096	6/12, 1/10	.601"	65 x .010" (12ga.)	•	•	•	•	•	•	•
			105 x .010" (10ga.)	•	•	•	•	•	•	•
100' (30.5 m)										
69087	4/14	.444"	41 x .010"	•	•	•	•	•	•	•
69092	6/14	.562"	41 x .010"	•	•	•	•	•	•	•
69094	7/14	.562"	41 x .010"	•	•	•	•	•	•	•
69099	6/14, 1/12	.565"	41 x .010" (14ga.)	•	•	•	•	•	•	•
			65 x .010" (12ga.)	•	•	•	•	•	•	•
66097	6/12, 1/10	.601"	65 x .010" (12ga.)	•	•	•	•	•	•	•
			105 x .010" (10ga.)	•	•	•	•	•	•	•
500' (152 m)										
69088	4/14	.444"	41 x .010"	•	•	•	•	•	•	•
69093	6/14	.562"	41 x .010"	•	•	•	•	•	•	•
69095	7/14	.562"	41 x .010"	•	•	•	•	•	•	•
69128	6/14, 1/12	.565"	41 x .010" (14ga.)	•	•	•	•	•	•	•
			65 x .010" (12ga.)	•	•	•	•	•	•	•
69098	6/12, 1/10	.601"	65 x .010" (12ga.)	•	•	•	•	•	•	•
			105 x .010" (10ga.)	•	•	•	•	•	•	•

ABS Trailer Cable (PVC)

This trailer cable exceeds SAE J2394 cable requirements. Specially designed for ABS brake system power requirements on single or multiple trailer configurations, the green outer jacket resists abrasion and oil contaminants and remains flexible at -70°C (-94°F).



Conductors/ Gauge	Outside Diameter	Stranding	Yellow	Red	Green	Brown	Black	Blue	White
Part # 69494 50' (15.2 m) Spool									
4/12	.068	65 x .010"	•	•	•	•	•	•	•
2/10	.068	105 x .010"	•	•	•	•	•	•	•
1/8	.068	168 x .010"	•	•	•	•	•	•	•
Part # 69493 100' (30.5 m) Spool									
4/12	.068	65 x .010"	•	•	•	•	•	•	•
2/10	.068	105 x .010"	•	•	•	•	•	•	•
1/8	.068	168 x .010"	•	•	•	•	•	•	•
Part # 69492 500' (152 m) Spool									
4/12	.068	65 x .010"	•	•	•	•	•	•	•
2/10	.068	105 x .010"	•	•	•	•	•	•	•
1/8	.068	168 x .010"	•	•	•	•	•	•	•

Replacement Socket & Plug

Repair or construct your own extension cords.
(5 per pack)



Part #	
69758	Male plug, 3 conductor, 110 volt
69759	Female socket, 3 conductor, 110 volt

Neoprene Jacketed Extension Cable

Extra flexible type SJOW jacket cable for use as power supply for machine tools and drills as well as general shop where subjected to hard usage in a damp or dry location. Oil and flame retardant. CSA and USL approved.



Part #	Conductors/ Gauge	Outside Diameter	Stranding	Volts
250' (76 m)				
69039	3/18	.305"	16 x .010"	300
69033	3/16	.330"	26 x .010"	300
69034	2/14	.340"	41 x .010"	300
69035	3/14	.365"	41 x .010"	300

Wire & Cable Tools



Heavy Duty Wire Stripper

Strip and cut 10-26 gauge wire without damaging the conductor. Crimps insulated and non-insulated terminals with ease.

Part #	
69967	Heavy Duty Wire Stripper



Dual Use Stripper/Cutter

This European designed stripper/cutter quickly and accurately strips wire from 10 - 22GA. Able to convert from stripper to cutter with a slide of the thumb. This tool is very easy to use with very limited strain.

Part #	
95725	Dual Use Stripper/Cutter

Wire & Cable Tools (continued...)

CR-300



Ratchet tool crimps insulated terminals from #22-10 AWG.

CR-100



Crimps insulated & non insulated terminals from #22 to #10 AWG. Includes stripper and bolt cutter.



Cable Stripper

Ideal for stripping a full range of cable from 8GA to 4/0GA.

Part #	
95721	Cable Stripper



Compact Cable Cutter

Easily cuts all cable sizes up to 2/0 GA. Approximately 8" long

Part #	
95712	Compact Cable Cutter

Compact Universal Crimping Tool

Ideal for crimping battery terminals from 8GA (heavy duty only for 8GA) to 1/0GA. Approximately 16" long



Part #	
95728	Compact Universal Crimping Tool

Cable Cutter

The long handle provides excellent leverage for cutting large cable up to 350 MCM. Approximately 18" long



Part #	
95714	Cable Cutter

Universal Crimping Tool 8GA-4/0

"Mechanics choice" for crimping battery terminals from 8GA to 4/0GA. Approximately 25" long



Part #	
95731	Universal Crimping Tool 8GA-4/0