

Work Lights & Cord Reels



Alert Electrical Products

Quality you can depend on is engineered into our Alert® line of work lights, extension cords, and cord reels. Heavy duty professional and industrial units have all the features demanded by mechanics, technicians and contractors.

ALL ALERT PRODUCTS SOLD IN CANADA HAVE CUL OR CSA APPROVAL.
For a detailed parts list, contact customer service.



Incandescent Worklights



BL-15

12
volt



PRO LITE™ SPECIALTY INCANDESCENT LIGHTING					
Part #	Description	Bulb	Cord Length	Wire Gauge	Max Rating
BL-15	12 Volt Automotive Work Light with Battery Clamps. Special Bulb Included. On-Off Switch in Handle. Swivel Hook.	60W, 12V included	15 ft	18/2	12V DC



TL-25P



TL-50GM



PRO LITE™ INCANDESCENT WORK LIGHTS						
Part #	Description	Outlet	Bulb	Cord Length	Wire Gauge	Max Rating
TL-25P	On-Off Switch, Plastic Swing Open Guard Swivel Hook	N/A	75W	25 ft	18/2	75W 125V
TL-50GM	On-Off Switch, Grounded Swing Open Metal Guard, Fixed Hook	Built In	100W	50 ft	16/3	1625W 13A 125V

*Bulb not included - Maximum bulb rating shown.



TL-25GM-CB



TLP-25GM-CB
TLP-50GM-CB



PRO LITE™ PROFESSIONAL INCANDESCENT WORK LIGHTS						
Part #	Description	Outlet	Bulb	Cord Length	Wire Gauge	Max Rating
TL-25GM-CB	On-Off Switch, Grounded Swing Open Metal Guard, Fixed Hook	Built-in w/circuit breaker	100W	25 ft	16/3	1625W 13A 125V
TLP-25GM-CB	On-Off Switch, Grounded Metal Guard 360° Rotary Hook, All Weather Cord	Built-in w/circuit breaker	100W	25 ft	16/3	1625W 13A 125V
TLP-50GM-CB	On-Off Switch, Grounded Metal Guard 360° Rotary Hook, All Weather Cord	Built-in w/circuit breaker	100W	25 ft	16/3	1625W 13A 125V

*Bulb not included - Maximum bulb rating shown.



HTL-25M-CB
HTL-50M-CB



PRO LITE™ INDUSTRIAL INCANDESCENT WORK LIGHT						
Part #	Description	Outlet	Bulb	Cord Length	Wire Gauge	Max Rating
HTL-25M-CB	Grounded Metal Reflector With Heavy Duty Metal Reflector/Bulb Guard, On-Off Switch, "Power On" Plug	Built-in w/circuit breaker	100W	25 ft	14/3	1875W 15A 125V
HTL-50M-CB	Grounded Metal Reflector With Heavy Duty Metal Reflector/Bulb Guard, On-Off Switch, "Power On" Plug	Built-in w/circuit breaker	100W	50 ft	14/3	1875W 15A 125V

*Bulb not included - Maximum bulb rating shown.



TLS-50
TLS-100



PRO LITE™ INDUSTRIAL INCANDESCENT WORK LIGHT						
Part #	Description	Outlet	Bulb	Cord Length	Wire Gauge	Max Rating
TLS-50	Molded-on Weather Resistant Lamp Sockets With Durable Plastic Bulb Guards Spaced On 10 Foot Centres. Linkable.	Built-in	5x 150W	50 ft	12/2	2500W 15A 125V
TLS-100	Grounded Metal Reflector With Heavy Duty Metal Reflector/Bulb Guard, On-Off Switch, "Power On" Plug	Built-in	10x 150W	100 ft	12/3	2500W 15A 125V

*Bulb not included - Maximum bulb rating shown.



900GP-CB



5000A-30G
5000A-30G-CB
5000-50G-CB



5000-35G-SSP



PRO REEL™ INCANDESCENT RETRACTABLE CORD REEL WORK LIGHTS						
Part #	Description	Outlet	Bulb	Cord Length	Wire Gauge	Max Rating
900GP-CB	High Impact Plastic Reel Housing, Grounded Metal Guard, On-Off Switch	Built-in w/circuit breaker	75W	20 ft	18/3	875W 7A 125V
5000A-30G	Powder Coated Metal Reel Housing, Grounded Metal Guard, On-Off Switch	Built-in	75W	30 ft	16/3	1250W 10A 125V
5000-50G-CB	Powder Coated Metal Reel Housing, Grounded Metal Guard, On-Off Switch	Built-in w/circuit breaker	75W	50 ft	18/3	875W 7A 125V
5000A-30G-CB	Powder Coated Metal Reel Housing, Grounded Metal Guard, On-Off Switch	Built-in w/circuit breaker	75W	30 ft	16/3	1250W 10A 125V
5000-35G-SSP	Powder Coated Steel Reel With Auto Switching Feature, Nylon Guard	N/A	75W	30 ft	18/3	1250W 10A 125V

*Bulb not included - Maximum bulb rating shown.



8050M-W



PRO REEL™ INDUSTRIAL INCANDESCENT RETRACTABLE CORD REEL WORK LIGHT						
Part #	Description	Outlet	Bulb	Cord Length	Wire Gauge	Max Rating
8050M-W	Industrial Grade Reel Housing. Quick Release Mounting Bracket. Convenient Carrying Handle. 360° Reflector Guard With Rotary Hook.	Built-in w/circuit breaker	100W	50 ft	14/3	1625W 13A 125V

*Bulb not included - Maximum bulb rating shown.

Extension Cords & Cord Reels



WC-625
WC-650
WC-6100



WRAP-N-CARRY™ SINGLE OUTLET EXTENSION CORDS					
Part #	Description	Outlets	Cord Length	Wire Gauge	Max Rating
WC-625	25 Feet of 16/3 Cord	Single	25 ft	16/3	1625W 13A 125V
WC-650	50 Feet of 16/3 Cord	Single	50 ft	16/3	1625W 13A 125V
WC-6100	100 Feet of 16/3 Cord	Single	100 ft	16/3	1250W 10A 125V



5000A-30GF



6000-25G



PRO REEL™ RETRACTABLE EXTENSION CORD REELS					
Part #	Description	Outlets	Cord Length	Wire Gauge	Max Rating
5000A-30GF	Powder Coated Metal Retractable Cord Reel Housing	Built-in	30 ft	16/3	1250W 10A 125V
6000-25G	Portable Wind-Up Multi Plug Reel, Convenient Carrying Handle.	Built-in w/circuit breaker	50 ft	16/3	1625W 13A 125V



5000A-30GF-CB
5000M-30GF-CB



PRO REEL™ RETRACTABLE EXTENSION CORD REELS					
Part #	Description	Outlets	Cord Length	Wire Gauge	Max Rating
5000A-30GF-CB	Powder Coated Metal Retractable Cord Reel Housing, Power Block	Built-in w/circuit breaker	30 ft	16/3	1250W 10A 125V
5000M-30GF-CB	Powder Coated Metal Retractable Cord Reel Housing, Power Block	Built-in w/circuit breaker	30 ft	14/3	1625W 13A 125V



8040T-P
8050M-P



PRO REEL™ INDUSTRIAL RETRACTABLE EXTENSION CORD REELS					
Part #	Description	Outlets	Cord Length	Wire Gauge	Max Rating
8040T-P	Heavy-Duty Industrial Grade Reel Housing. Quick Release Mounting Bracket. Convenient Carrying Handle. Power Block.	Built-in w/circuit breaker	40 ft	12/3	1875W 15A 125V
8050M-P	Heavy-Duty Industrial Grade Reel Housing. Quick Release Mounting Bracket. Convenient Carrying Handle. Power Block.	Built-in w/circuit breaker	50 ft	14/3	1625W 13A 125V



5000-40PL-SSP

NEW



13RF-30GR



PRO Δ REEL™ PROFESSIONAL FLUORESCENT WORK LIGHT CORD REEL						
Part #	Description	Outlet	Rep. Bulb	Cord Length	Wire Gauge	Max Rating
5000-40PL-SSP	Powder Coated Steel Reel With Auto Switching Feature. Shatter Resistant Lamp Housing. 360° Swivel Hanging Hook.	N/A	189194	40 ft	18/2	13W .305A 125V
13RF-30GR	Powder Coated Steel Reel Housing. Ballast & On-Off Switch Built in Handle. 360° Adjustable Hanging Hook. Polycarbonate Lens With 270° Arc of light. Adjustable Magnet Mounting Clip Adheres to Most Metal Surfaces.	Built-In w/Circuit Breaker	189194	30 ft	18/2	1250W 10A 125V LAMP RATING .305A 125V



8050A-FL



PRO Δ REEL™ INDUSTRIAL FLUORESCENT WORK LIGHT CORD REEL						
Part #	Description	Outlet	Rep. Bulb	Cord Length	Wire Gauge	Max Rating
8050A-FL	Individual On-Off Switches, Adjustable Front & Rear Hanging Hooks, Magnet Clip. Heavy-Duty Industrial Grade Reel Housing. Quick Release Bracket	Built-In w/Circuit Breaker	2x 189194	50 ft	16/3	875W 7A 125V

Halogen Worklights



HR-15



HC-20
12
volt



PRO Δ LITE™ HALOGEN WORK LIGHTS					
Part #	Description	Replacement Bulb	Cord Length	Wire Gauge	Max Rating
HR-15	90° Swivel Head, 360° Adjustable Hanging Hook, On-Off Switch Built Into Handle, Compact Design.	189197	15 ft	18/2	20W .17A 125V
HC-20	90° Swivel Head, 360° Adjustable Hanging Hook, On-Off Switch Built Into Handle, Compact Design.	189197	20 ft	18/2	20W 12V DC



HBL-12

NEW



LBL-12



PRO Δ LITE™ HALOGEN WORK LIGHTS					
Part #	Description	Replacement Bulb	Cord Length	Wire Gauge	Max Rating
HBL-12	Multi-Adjustable Bright 12 Watt Lamp. On-Off Switch Built Into Adjustable Arm. 12 Volt Power Transformer. Accessory Magnetic Base Allows Lamp to Cling To Most Metal Surfaces	189196	6 ft	24/2	60HZ 125V
LBL-12	Above in kit form with extra table bracket and spare bulb.	189196	6 ft	24/2	60HZ 125V

Fluorescent Worklights



EPL-15



15F-25



PRO LITE™ FLUORESCENT WORK LIGHTS						
Part #	Description	Replacement Bulb	Cord Length	Wire Gauge	Max Rating	
EPL-15	Ballast & On-Off Switch Built in Handle. Polycarbonate Lens With 270° Arc of light. Shatter Resistant Housing. 360° Adjustable Hanging Hook.	189194	15 ft	18/2	13W .350A 125V	
15F-25	On-Off Switch in Handle. Plug in Ballast. Shatter Resistant Housing. Non-Glare Reflector. 360° Swivel Hanging Hook. 2 Additional Hooks for Horizontal Hanging.	189195	25 ft	18/2	13W .350A 125V	
EPL-25NS	Same as EPL-15 but with 25 ft cord and no switch.	189194	25 ft	18/2	13W .350A 125V	

UPL-25G
UPL-50G



15FG-25



QPL-8



PRO LITE™ PROFESSIONAL FLUORESCENT WORK LIGHTS						
Part #	Description	Outlet	Replacement Bulb	Cord Length	Wire Gauge	Max Rat
UPL-25G	Grounded Outlet, Ballast & On-Off Switch Built in Handle. Adjustable Hanging Hook. 360° Rotating Magnet Clings to Most Metal Surfaces.	Built-in w/circuit breaker	189194	25 ft	16/3	1625W 13A 125V
UPL-50G	Grounded Outlet, Ballast & On-Off Switch Built in Handle. Adjustable Hanging Hook. 360° Rotating Magnet Clings to Most Metal Surfaces.	Built-in w/circuit breaker	189194	50 ft	16/3	1625W 13A 125V
15FG-25	Grounded Outlet, Ballast & On-Off Switch Built in Handle. Adjustable Front & Rear Hanging Hooks. 2 Adjustable Mounting Stands. Non-Glare Reflector.	Built-in w/circuit breaker	189195	25 ft	16/3	1625W 13A 125V
QPL-8	2 On-Off Switches, Adjustable Free Standing Base, Built in Hanging Hook swivels 360°.	N/A	4x 189194	8 ft	18/2	1625W 13A 125V

DPL-25G



PRO LITE™ INDUSTRIAL FLUORESCENT WORK LIGHTS						
Part #	Description	Outlet	Replacement Bulb	Cord Length	Wire Gauge	Max Rating
DPL-25G	Individual On-Off Switches, Adjustable Front & Rear Hanging Hooks, Magnet Clip	Built-in w/circuit breaker	2x 189194	25 ft	16/3	1625W 13A 125V

13RPL-20E



13RPL-20E



PRO REEL™ FLUORESCENT WORK LIGHT CORD REEL						
Part #	Description	Replacement Bulb	Cord Length	Wire Gauge	Max Rating	
13RPL-20E	Retractable Cord Reel With Durable Shatter Resistant Reel & Lamp Housing. Plug in Ballast, On-Off Switch Built Into Handle. Adjustable Hanging Hook.	189194	20 ft	18/2	13W .350A 125V	
13RPL-40	Retractable Cord Reel, On-Off Switch & Ballast Built Into Lamp Handle. Adjustable Hanging Hook. Powder Coated Metal Reel Housing.	189194	40 ft	18/2	13W .350A 125V	

Cord Storage & Replacement Bulbs



500-W



7000-W



WRAP-N-CARRY™ - PRO Δ REEL™ CORD STORAGE DEVICES	
Part #	Description
500-WR	Stores Up to 100 Feet Of 16/3 Electrical Cord. Built In Storage Compartments In Each End Of Cord Tender. May Also Be Used For Storage Of Rope, Wire, Yarn, Etc.
7000-WR	Stores Up to 100 Feet Of 12/3, 125 Feet Of 14/3, 150 Feet Of 16/3, Electrical Cord. May Be Mounted On Wall With Brackets Included. May Also Be Used For Storage Of Rope, Air Hose, Etc.



PL-13 Bulb
(#189194)



MR-16 Bulb
(#189197)

PRO Δ LITE™ - PRO Δ REEL™ REPLACEMENT BULBS & ACCESSORIES	
Part #	Description
189194	13 Watt PL. Lamp - For Use With EPL, UPL, QPL, DPL Models.
189195	15 Watt Fluorescent Lamp - For Use With 15F-25 and 15FG-25 Models
189196	12 Watt Halogen Lamp - For Use With HBL-12 Models.
189197	20 Watt Halogen Lamp - For Use With HR-15 & HC-20 Models.

MMC-1 - Included with most professional models or may be purchased separately to upgrade the following EPL-15, HR-15, HC 20, 13RPL-20E.

Air Hose Reels



PR-304
PR-308
PR-508
PR-508R



AIRE CRAFT™ RETRACTABLE AIR HOSE REELS			
Part #	Hose Dia.	Hose Length	Description
PR-304	1/4 in.	30 ft.	Premium PVC Hose Resists Oil & Abrasion. 3 ft. Lead In Hose Included. NPT Brass Hose Connections. 300 PSI/20 BAR Max. Working Pressure. Rugged Drive Spring For Smooth Retraction. Auto Locking Mechanism. Use Indoor or Outdoor. 180° Quick Release Mounting Bracket. Includes Hose.
PR-308	3/8 in.	30 ft.	Premium PVC Hose Resists Oil & Abrasion. 3 ft. Lead In Hose Included. NPT Brass Hose Connections. 300 PSI/20 BAR Max. Working Pressure. Rugged Drive Spring For Smooth Retraction. Auto Locking Mechanism. Use Indoor or Outdoor. 180° Quick Release Mounting Bracket. Includes Hose.
PR-508	3/8 in.	50 ft.	Premium PVC Hose Resists Oil & Abrasion. 3 ft. Lead In Hose Included. NPT Brass Hose Connections. 300 PSI/20 BAR Max. Working Pressure. Rugged Drive Spring For Smooth Retraction. Auto Locking Mechanism. Use Indoor or Outdoor. 180° Quick Release Mounting Bracket. Includes Hose.
PR-508R	3/8 in.	50 ft.	Same as PR508 but with 50ft of rubber hose.



PW-50
PW-100



AIRE CRAFT™ MANUAL AIR HOSE REELS		
Part #	Hose Length	Description
PW-50	50 ft.	Holds 3/8" I.D. Hose. 3/8" Brass NPT Fittings. 250 PSI/16.7 BAR Max. Working Pressure. Heavy-Gauge Steel Reel Frame, Spool & Drum. Corrosion Resistant Powder Coated Finish. Drag Spring Reduces Self Unwinding. Suitable for Indoor or Outdoor Use. Includes Mounting Bracket. Does Not Include Hose.
PW-100	100 ft.	Holds 3/8" I.D. Hose. 3/8" Brass NPT Fittings. 250 PSI/16.7 BAR Max. Working Pressure. Heavy-Gauge Steel Reel Frame, Spool & Drum. Corrosion Resistant Powder Coated Finish. Drag Spring Reduces Self Unwinding. Suitable for Indoor or Outdoor Use. Includes Mounting Bracket. Does Not Include Hose.